

# Daugherty Township

2182 Mercer Road, New Brighton, PA 15066

PH: (724)846-5337 Fax: (724)846-6481

[www.daughertytownship-pa.gov](http://www.daughertytownship-pa.gov)

[daughertytownship@comcast.net](mailto:daughertytownship@comcast.net)



---

## APPLICATION FOR ROAD OPENING PERMIT

Application No. \_\_\_\_\_ Date Received \_\_\_\_\_

### Applicant Information

Applicant Name \_\_\_\_\_

Applicant Status (Check) \_\_\_\_\_ Owner \_\_\_\_\_ Utility Company \_\_\_\_\_ Agent \_\_\_\_\_ Other

Name/Address of Owner or Utility Company

Name/Address of Agent or Other

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Phone No. \_\_\_\_\_

Phone No. \_\_\_\_\_

### Contractor Information

Name/Address of Contractor

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Phone No. \_\_\_\_\_

### Location Information

Address \_\_\_\_\_

Tax Parcel No. \_\_\_\_\_

Start Date: \_\_\_\_\_

Proposed Completion Date: \_\_\_\_\_

PA One Call Serial # \_\_\_\_\_

### Road Opening Information

Reason for Road Opening: \_\_\_\_\_

Location of Opening: \_\_\_\_\_

Size of Opening: Length: \_\_\_\_\_ Width: \_\_\_\_\_ Depth: \_\_\_\_\_

Distance from nearest intersection: \_\_\_\_\_ ft. Distance from nearest driveway(s): \_\_\_\_\_ ft.

Distance from center line of roadway to edge of paving \_\_\_\_\_ ft.

Approximate area of opening in the improved road surface \_\_\_\_\_ sq. yds.

Will the improved surface of the road be opened?  YES  NO

If yes, why is it not possible to bore under the road? \_\_\_\_\_

### **PA One Call**

**CALL BEFORE YOU DIG!!!** [www.paonecall.org](http://www.paonecall.org)

Or dial **811** to access you local one-call center.

Pennsylvania law requires that you call before excavation.

Please provide 10 to 90 days' notice in the design stage.

Please provide 3 to 10 days' notice before you dig.

PA ONE CALL SERIAL NUMBER (ATTACH COPY OF FORM) \_\_\_\_\_

### **Applicant Acknowledgement**

**I hereby acknowledge that the above information is true and correct to the best of my knowledge and belief.**

\_\_\_\_\_  
Print Name

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date

The following **MUST** be submitted to be considered a **COMPLETE** application:

1. Submit a completed Application for Road Opening Permit.
2. Submit two (2) copies of the Include 3 copies of all specifications of materials and methods used.
3. Show all dimensions/extent of trenching, or work to be done.
4. Indicate if traffic control measures are required and what they will be.
5. Any work that enters a State Right-of Way will require a State Permit; include 2 copies of a State Permit.
6. Submit a Certificate of Insurance showing proof of General Liability and Workers Compensation Insurance for work performed by a general contractor.
7. Submit the required application fee in the amount of \$100.00.
8. Submit a repair/ replacement deposit in accordance with § 145-3B1 of the Code of the Township of Daugherty. Minimum deposit shall be \$100.00.

### **NO CONSTRUCTION TO TAKE PLACE BEFORE FEES PAID AND INSPECTION**

NOTE: Permits are valid for one year from date of issue.

**BASIC CHECKLIST FOR CONCRETE APRONS, CURBS AND/OR SIDEWALKS. FOLLOW SPECIFICATIONS IN PENNDOT 408.**

- Permit issued after fee is paid.
- All work to conform to PENNDOT 408 standards.
- Material dug out to correct depth – use straight edge or string line to check.
- PENNDOT 408 specification 7x8x18 inch curb forms with an 8 inch reveal to be used and pinned correctly. No straight forms to be used.
- Expansion joint material shall be ½ inch wide pre-molded expansion joint material.
- ½ inch expansion joint material must be available for when concrete arrives, all edges to be straight saw cut the full depth of pavement where joint materials are to be placed.
- Minimum 6 inches of PADOT 2A modified stone compacted in place under where concrete is to be poured (apron, curbs or sidewalk).
- #5 rebar must be available and used where depressed curb will be placed.
- Depressed curb to have 2 #5 rebar placed in the curb, 5 inches from the bottom and each bar being placed 1-1/2 inches in from the outside edges (5 inch spacing between the rebar), minimum 11-1/2 inches thickness (depth of depressed curbing).
- Expansion joint material to be placed between curb and driveway apron.
- 6 x 6 inch welded wire mesh to be placed throughout driveway apron, wire mesh to be minimum 10 gauge material placed on chairs in the middle of material depth.
- Concrete in driveway apron to be a minimum of 6 inches thick, must use 4000 psi air entrained concrete, this includes the sidewalk area, which is part of the driveway.
- Concrete sidewalks to be minimum 4 inches thick, must use 4,000 psi air entrained concrete.
- All joints between concrete apron and bituminous pavement shall be sealed with a PENNDOT approved crack sealer.
- Concrete curbing joints to be clean cut 2 inches in depth and every 10 linear feet, with an expansion joint every 60 linear feet or less, at structures and at the end of every work day.
- Sidewalk joints to be clean cut 1 inch in depth, every 5 feet with an expansion joint every 30 feet or less, at structures and at the end of each work day.
- Concrete to have a float finish, except where slope is 10% or greater where it shall have a broom finish.
- Only honeycomb areas may be patched using 1 part concrete and 2 parts sand, or its equal.
- NO MONOLYTHIC POURS PERMITTED.
- Use PENNDOT material and application specifications for blacktop. 5 inch base coat, 2 inch binder course and 1-1/2 inch wearing course.

**CALL 724-846-5337 TO SCHEDULE AN INSPECTION  
24 HOUR NOTICE IS REQUIRED FOR ALL INSPECTIONS  
NO CONCRETE IS TO BE POURED BEFORE INSPECTION**